

## Wired ADSL2+ Modem Router



### KD319RI Features:

- **High Speed:** Downstream rates up to 24Mbps and upstream rates up to 1Mbps
- **Operating distance:** up to 5KM
- **1-Fast Ethernet Port:** One LAN Port provide interface for computer or other network device.
- **TR-069:** Manage settings and updates remotely from any end equipment
- **Compatibility:** Interoperable with all major DSLAM equipments
- **QOS :** Quality of Service control for traffic prioritization and bandwidth management
- **Simple set up with GUI:** GUI makes installation easier and faster

# Specifications

## BASICS

<b>Operation Mode:</b>	ADSL2+ Modem Router
<b>Speed:</b>	Rate Adaptive: 32 Kbps steps
<b>Standard:</b>	Full-rate ANSI T1.413 issue 2 ITU-T G.992.1 /2/3/4/5 ITU-T G.994.1 (G.hs)
<b>WAN Connection Type</b>	DHCP ,Static IP, PPPoE, PPPoA, IPoA, Bridge

## SOFTWARE

<b>Protocol Support:</b>	Static IP, Dynamic RIP support DMZ support Network Address Translation (NAT) PVC Port Mapping (Ethernet ports) Port Mapping/Forwarding NAT Application Level Gateway for popular applications DHCP Server/Relay/client DNS Relay Agent SNMPv1.0 support TR069 CWMMP PPP Auto Reconnect and configurable timeouts PPP Auto Reconnect on WAN Access/PPP on Demand IGMP Multicast
<b>Security Support:</b>	PAP/CHAP Authentication for PPP mode NAT for Firewall Packet Filtering Firewall Support 2 Level (User/Admin) Authentication to Router IP and MAC Filtering
<b>Management Support:</b>	Web Based GUI FTP /HTTP/Telnet/TR069 /SNMP v1.0 Firmware upgrade-able
<b>ATM, PTM and PPP Features</b>	RFC2684 /2364 /2516 /2225/1577 / 1483/2684 ATM Forum UNI 3.1/4.0 PVC VPI Range (0-255) and VCI range (32-65535) UBR, CBR F4/F5 OAM Loopback
<b>VPN:</b>	IPSec /PPTP /L2TP pass through
<b>Port Forwarding:</b>	Virtual server, Port Triggering, DMZ, ALG
<b>DHCP:</b>	Server, Client, DHCP Client List Address Reservation, DHCP relay
<b>QOS:</b>	Priority Queuing Classification Rules 802.1p
<b>IPv6:</b>	IPv4 and IPv6 dual stack

## HARDWARE

<b>Physical Interface:</b>	1 *FE LAN, 1*DSL RJ11 port
<b>Buttons:</b>	Power/Reset
<b>Power</b>	Input: 100-240V AC,50Hz
<b>LED Indicators:</b>	Power, LAN, DSL, INET
<b>Processor</b>	RTL8271SR+RTL8271
<b>Memory</b>	2MB flash and 8MB RAM

## OTHERS

<b>Operation System:</b>	Windows 7,8,XP, VISTA/Macintosh/Linux
<b>Package Content:</b>	Power Plug x 1, Installation Manual x 1, RJ11 cable x 1 RJ45 cable x 1, External splitter x 1
<b>Environment:</b>	Operating Temperature: 0°C~40°C(32~104°F) Storage Temperature: -30°C~60°C(-22~140°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing
<b>Dimension:</b>	4.17*3.27*1.26 in (106*83*32mm)
<b>Weight:</b>	0.33 lbs (150g)
<b>Warranty</b>	One year

## Interface:



## Package Content:



## Related products:



**KW58293 ADSL2+ Modem Router**

Internal 2T2R  
1\* DSL port  
4 \*Fast LAN port  
300Mbps Wi-Fi Speed



**KW58283 ADSL2+ Modem Router**

External 2T2R  
1 \*USB  
1\*DSL port  
4 \*Fast LAN port  
300Mbps Wi-Fi Speed



**KW5863 ADSL2+ VoIP Gateway**

External 2T2R  
1 \*USB  
2\* FXS port  
1\*DSL port  
4 \*Fast LAN port  
300Mbps Wi-Fi Speed