



KS105 Switch User Manual

Shenzhen Kasda Digital Technology Co., LTD

Content

Chapter 1. Introduction of the Product	3
1.1 Overview of the Product.....	3
1.2 Features.....	3
Chapter 2. Installation.....	3
2.1 Mounting the Switch on a Desk.....	3
2.2 Power On	4
Chapter 3. Identifying External Components	4
3.1 Front Panel.....	4
3.2 Rear Panel.....	5
Chapter 4. Package Contents	6
Appendix A: Specifications	6
Appendix B: Troubleshooting	7

Chapter 1. Introduction of the Product

Thank you for choosing the KS105 10/100Mbps Desktop Switch.

1.1 Overview of the Product

The KS105 architecture is the optimal solution for consumer switching needs with its support for high-performance line rate capabilities and ability to identify and prioritize different data packet types within the switch while simultaneously assigning voice packets a higher priority for outbound communications. The KS105 is poised to drive FE into the unmanaged and Smart switch, WLAN router, and CPE/Gateway markets with its comprehensive Layer 2 feature set, support for both DSL/cable modem and WLAN connectivity, and an industry-leading 5 FE of switching capacity—all on a single chip.

1.2 Features

- Complies with IEEE 802.3, IEEE 802.3u standards

- 5 10/100Mbps Auto-Negotiation RJ45 ports supporting Auto-MDI/MDIX

- Supports IEEE802.3x flow control for Full Duplex mode and backpressure for Half Duplex mode

- Supports MAC address auto-learning and auto-aging

- LED indicators for monitoring power, link, activity

- Plastic case, desktop or wall-mounting design

- External Power Adapter supply

Chapter 2. Installation

2.1 Mounting the Switch on a Desk

To install the Switch, please follow the steps:

- 1) You can place the Switch on a flat desk.
- 2) Please inspect the Power Adapter carefully and make sure that it is properly connected to a power source.
- 3) Ensure adequate ventilation space around the switch for dissipating heat and air.

Note:

Please avoid any heavy thing placed on the switch.

2.2 Power On

Powering on the Switch, it will automatically initialize and its LED indicators will respond as follows:

- 1) All of the Link/Act LED indicators will flash momentarily, which represents a resetting of the system.
- 2) The Power LED indicator will light all the time.

Note:

If the LED indicators don't respond as described above, please check the power supply and its connection.

Chapter 3. Identifying External Components

This Chapter describes the front panel, rear panel and LED indicators of the Switch.

3.1 Front Panel



Figure 3-1 KS105 Switch Front Panel

The Switch's LEDs are located on the front panel.

Power LED: This indicator will light up when the Switch powers on.

LANs (1-5): LED indicator will light green when a device is connected to the corresponding port. It flashes when data is being transmitted or received on the connection.

3.2 Rear Panel



Figure 3-2 KS105 Switch Rear Panel

The following parts are located on the rear panel:

Power: The Power socket is where you will connect the power adapter.

Please use the power adapter provided with this KS105 Switch.

LAN (1-5): The KS105 Switch is equipped with 5 10/100Mbps Auto-Negotiation RJ45 ports where you will connect your network devices.

The working status can be indicated by the corresponding LEDs on the front panel.

Chapter 4. Package Contents

The following items should be found in your box:

One KS105 Switch
One Power Adapter
One CD

Note:

Make sure that the box contains the above items. If any of the listed items are damaged or missing, please contact with your distributor.

Appendix A: Specifications

Standards and Protocols	IEEE 802.3, 802.3u, 802.3x CSMA/CD, TCP/IP
Basic Function	Wire-speed Performance MAC Address Auto-learning and Auto-aging IEEE 802.3x flow control for full-duplex mode and backpressure for half-duplex mode
MAC Address Table	1k
Forwarding Rate	10BASE-T: 14880pps/port 100BASE-TX: 148800pps/port
Transmission Method	Store-and-Forward
Ports	5 10/100Mbps Auto-Negotiation RJ45 ports (Auto MDI/MDIX)
Network Media	10Base-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 100Base-Tx: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
LED Indicators	Power, LAN1-5
Safety and Emission	FCC, CE
Environment	0°C ~40°C (32°F~104°F) -40°C ~70°C (-40°F ~158°F) 10%~90% non-condensing 5%~90% non-condensing
Power	External Power Adapter

Appendix B: Troubleshooting

1. The Power LED is not lit

Check to see if the power cord is connected to the Switch properly, and make sure the power source is ON.

2. The LAN LED is not lit when a device is connected to the corresponding port

Check to see if the cable connectors are firmly plugged into the Switch and the device, and verify the connected device is turned on and working well. Make sure the cable is not longer than 100 meters (328 feet)