



























KW9621 Dual WAN 4G Router

Features:

MIMO Tech— Two external antennas to deliver the best wireless signal, fully expand coverage

Simple set up with GUI—friendly GUI makes installation easier and faster

2.4G 300Mbps Wi-Fi Speed—low latency for multiple user access

Breakthrough speeds with 4G LTE technology

TD-LTE uplink up to 30Mbps, downlink up to 130Mbps FDD-LTE uplink up to 50Mbps, downlink up to 150Mbps

Your mobile internet service for home and office

GSM, TS-SCDMA, WCDMA, FDD-LTE, TD-LTE

Summary

KASDA KW9621 LTE WIFI ROUTER is perfect for you to stay connected to the Internet with fast data rates, low latency where Ethernet connection is not available.

Using the latest 4G LTE technology, you can achieve downlink speeds of up to 150 Mbps and uplink speeds of up to 50 Mbps.

Simply insert an USIM card into this device and get Internet access anywhere you can receive LTE,3G, GSM data signal. KW9621 also has two external antennas for a connection that is consistent and reliable.

300Mbps Wi-Fi speed makes lag free connection for notebooks and smart phones.



♦ Specifications

WIRELESS				
Operation Mode:	LTE router, Client Router, Access Point, Repeater.			
Speed:	Download speeds up to 150 Mbps Upload speeds up to 50 Mbps 11n speed up to 300Mbps			
Frequency Range:	2,4Ghz-2,4835Hhz			
Wireless Features:	IEEE802.11b/g/n 300Mbps Multi-SSID Access Control List 64/128-bit WEP WPA-PSK/WPA2-PSK/TKIP/AES			
SOFTWARE				
VPN:	IPSec /PPTP /L2TP			
Security Support:	Parental control PAP/CHAP Authentication for PPP mode NAT for Firewall SPI Firewall with DoS protection ALG for NAT/PAT support 2 Level (User/Admin) Authentication to Router IP Filtering and MAC Filtering			
Management Support:	Web Based GUI Remote Access Control FTP/HTTP Telnet Command Line Interface via serial interface Diagnostic Test Firmware upgrade-able			
HARDWARE				
Physical Interface:	1 Mini-PCle, 4 FE LAN, 1 FE WAN, 1 USIM port			
Flash and Memory	Flash up to 32Mb, Memory up to 256Mb			
Power	Input: 100-240V AC,50Hz Output: 12V DC,1A			
LED Indicators:	Power,LAN1/2/3/4,WLAN,WAN,Internet			
Built-in Battery:	3000mAh, working time up to 3 hours, 6 hours stand-by			
Antenna Gain: Maximum Connected Users:	3dBi			
Maximum Connected Users: 16 OTHERS				
Operation System:	Windows 7,8,XP, VISTA/Macintosh/Linux			
Package Content:	RJ45 cable x 1, Power Adapter x 1, Installation Manual x 1			
Environment:	Operating Temperature:-10°C~55°C(14~131°F) Storage Temperature: -30°C~60°C(-22~140°F) Operating Humidity: 5%~95% non-condensing Storage Humidity: 5%~90% non-condensing			
Dimension:	180(H)*115(W)*26(T)mm			
Weight:	180g			

2G	GSM	GSM 800MHz/ EGSM900 MHz / DCS1800 MHz / PCS1900 MHz		
3G	TD-SCDMA	BAND 34: 2000MHz 2010~2025MHz BAND 39: 1900MHz+ 1880~1920MHz		
		BAND 1 2100MHZ: upstream1920~1980 MHz downstream2110~2170 MHz BAND 2 1900MHz: upstream1850~1910MHz downstream1930~1990MHz	Upload Speed	5.76Mbps
	WCDMA	BAND 5 850MHz: upstream824~849MHz downstream869~894MHz BAND 8: 900HMz upstream 880~915MHz downstream 925~960MHz	Download speed	42Mbps
4G		BAND 1: 2100Mhz Range: UL 1920~1980MHz DL 2110~2170MHz BAND 3: 1800MHz Range: UL 1710~1785MHz	Uplink Speed	50Mbps
	FDD-LTE Cat4 BAND 7: 2	DL 1805~1880MHz BAND 7: 2600Mhz Range: UL 2500~2570MHz DL 2620~2690MHz	Downlink Speed	150Mbps
		BAND 38: 2600MHz Range:2570~2620MHz Width:50MHz BAND 39: 1900MHz Range:1880~1920MHz Width: 40Mhz	Uplink Speed	30Mbps
	TDD-LTE	BAND 40: 2350MHz Range:2300~2400MHz Width: 100MHz BAND 41: 2600MHz Range:2496~2690MHz Width: 194MHz	Downlink Speed	130Mbps

Note: For other particular band, e.g. Band 42, please send inquiry by email, KW9621 can be customized according to demands.

Related products:





FDD/TDD-LTE

TDS/WCDMA/GSM/GPRS/EDGE
2800mAh Li-ion battery

USB2.0/ SIM slot/1T1R internal

antenna/LED screen/Micro SD up to 32GB



KW9520 Mobile Wi-Fi Hotspot Router

FDD/TDD-LTE
TDS/WCDMA/GSM/GPRS/ EDGE
2800mAh Li-ion battery
Micro-SD slot Up to 32GB/SIM

slot/Micro-USB/Two external antenna ports



KW9620 Wi-Fi Hotspot router

FDD/TDD-LTE
TDS/WCDMA/CDMA/GSM/GPRS/EDGE
2Rx1T MIMO
2200mAh Li-ion battery
One FE WAN port/Four FE ports/One RJ11
port/USB 2.0 /USIM slot/T-Flash, up to
64GB